

Technical data BHA 170 AP C/C

Descrizione

Top-of-therange alternating volumetric pumps with four semi-hydraulic diaphragms forprofessional agricultural use on sprayers for high pressure pesticide sprayingin orchards and vineyards. Parts incontact with pumped liquids in anodised aluminium (BHA), Rilsan-coatedaluminium (BHP), nylon and stainless steel. Diaphragmsin NBR or Desmopan. Seals inNBR. Monoblockfrontal intake/delivery line to allow valves to be inspected or replacedwithout removing the pump from the sprayer.

Die-castcasing with extremely rugged oil-immersed mechanism and clear plastic tank forvisual level checking.

Pistonswith ring for a more efficient "oil cushion" system to protect the diaphragm. New-designdiaphragm cut-out system to prevent contact tearing even in heavy-dutyoperating conditions. Sphericalsector profile valves for lower flow resistance and improved volumetricefficiency.

Details	Value
ARCode	852
Category	ВНА
Product	BHA 170
Version	AP C/C
Number of diaph	4
Delivery (I/min)	160,4
Delivery (gpm)	42,4
Pressure (bar)	50
Pressure (psi)	725
Power (hp)	19,3
RPM	550
Weight (kg)	51
Dimensions (mm) L	467
Dimensions (mm) H	451
Dimensions (mm) W	418
Suction (mm)	ø 40
Outlet (mm)	ø 3/4 " G(M)
Temperature Max °C	60



Technical data BHA 170 AP C/C

